




Technical Information

Model AVF 40-3 LCD

Available in MirrorVision® only

Bezel size





<u>Model</u>	<u>Screen</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>
	<u>Size</u>	Overall Height	Overall Width	Cut out Height	Cut out Width	Max Depth
AVF-40-LCD	1016mm	692mm	1049mm	683mm	1040mm	135mm

<u>Screen</u>

LCD TFT
WXGA 1366 x 768
PAL/SECAM-B/G, D/K, L
Full Auto Tuning
TeleText/FastText
Heated Screen

Inputs

- I x HDMI (High Definition Multimedia Interface)
- I x Component in(Y/Pb/Pr) 480p/576p/720p/1080i
- 2 x Scart (1x Fully Wired, 1 x Half Wired)
- I x Composite AV (Yellow, Red, and White)
- I x S- Video
- I x PC D- Connecter + 3.5mm Audio
- I x Analogue Tuner
- I x Digital Tuner (Freeview with Cam card slot)

Sound

Nicam Stereo 2 x 10 Watts (RMS) Graphic Equaliser


Power

Auto sensing 90-240VAC IEC "Cold" input connector. Power Consumption I30W Standby Consumption <3w

Optional

Hard wired control panel with switch mimic connection.

Speaker details



Information was correct at time of printing and may be changed without prior notice.